

[Validate](#)[Print](#)[Help](#)

Percentage BoQ

Tender Inviting Authority: Senior Manager C.K.Pandey

Name of Work : Conversion of proposed F&B facilities of Mezzanine floor of halls 3 & 4 into the Conference Halls

Contract No:

Bidder Name :						
PRICE SCHEDULE (This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only) NOTE:- 1.The rates should be quoted inclusive of GST as applicable 2. The agency should file ECR against ESI & EPF for the individual workers engaged in ITPO & submit the same with bank certified copy, bill, wage sheet & attendance sheet etc. before payment. 3. Contractural Labour Act Registration if applicable.						
NUMBER #	TEXT #	NUMBER #	TEXT #	NUMBER	NUMBER #	TEXT #
Sl. No.	Item Description	Quantity	Units	Estimated Rate	TOTAL AMOUNT	TOTAL AMOUNT In Words
1	2	4	5	6	53	55
1	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete. Size of Tile 600x600 mm	1000.00	sqm	1500.55	1500550.00	INR Fifteen Lakh Five Hundred & Fifty Only
2	Providing and laying Vitrified tiles in different sizes (thickness to be specified by manufacturer), with water absorption less than 0.08 % and conforming to I.S. 15622, of approved make, in all colours & shade, in skirting, riser of steps, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joint with white cement & matching pigments etc. complete. Size of Tile 600x600 mm	20.00	sqm	1545.85	30917.00	INR Thirty Thousand Nine Hundred & Seventeen Only

3	Providing and fixing partition upto ceiling height consisting of G.I. frame and required board, including providing and fixing of frame work made of special section power pressed/ roll form G.I. sheet with zinc coating of 120 gms/ sqm(both side inclusive), consisting of floor and ceiling channel 50mm wide having equal flanges of 32 mm and 0.50 mm thick, fixed to the floor and ceiling at the spacing of 610 mm centre to centre with dash fastener of 12.5 mm dia meter 50 mm length or suitable anchor fastener or metal screws with nylon plugs and the studs 48 mm wide having one flange of 34 mm and other flange 36 mm and 0.50 mm thick fixed vertically within flanges of floor and ceiling channel and placed at a spacing of 610 mm centre to centre by 6 mm dia bolts and nuts, including fixing of studs along both ends of partition fixed flush to wall with suitable anchor fastener or metal screws with nylon plugs at spacing of 450 mm centre to centre, and fixing of boards to both side of frame work by 25 mm long dry wall screws on studs, floor and ceiling channels at the spacing of 300 mm centre to centre. The boards are to be fixed to the frame work with joints staggered to avoid through cracks, Galvanised M.S. fixing channel of 99 mm width (0.9 mm thick having two flanges of 9.5 mm each with zinc coating of 120 gms/sqm(both side inclusive)) to be provided at the horizontal joints of two boards, fixed to the studs using metal to metal flat head screws, including jointing and finishing to a flush finish with recommended jointing compound, jointing tape, angle beads at corners (25 mm x 25 mm x 0.5 mm), joint finisher and two coats of primer suitable for board as per manufacture's specification and direction of engineer in charge all complete. 66mm overall thickness Partition with 8mm thick double skin Calcium Silicate Board made with Calcareous & Siliceous materials reinforced with cellulose fiber manufactured through autoclaving process with Compressive Strength 225 kg/sq.cm, Bending Strength 100 kg./ sq.cm	200.00	sqm	1808.05	361610.00	INR Three Lakh Sixty One Thousand Six Hundred & Ten Only
4	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:5:10 (1 cement : 5 fine sand : 10 graded stone aggregate 40 mm nominal size)	35.00	cum	5225.15	182880.00	INR One Lakh Eighty Two Thousand Eight Hundred & Eighty Only
5	Providing and fixing ISI marked flush door shutters conforming to IS : 2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters: 35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws	10.00	sqm	1886.70	18867.00	INR Eighteen Thousand Eight Hundred & Sixty Seven Only
6	Extra for providing lipping with 2nd class teak wood battens 25 mm minimum depth on all edges of flush door shutters (over all area of door shutter to be measured).	10.00	sqm	401.40	4014.00	INR Four Thousand & Fourteen Only
7	Providing & fixing glass panes with putty and glazing clips in steel doors, windows, clerestory windows, all complete with : 5.5 mm thick glass panes	5.00	sqm	1194.85	5974.00	INR Five Thousand Nine Hundred & Seventy Four Only
8	Wall painting with acrylic emulsion paint of approved brand and manufacture to give an even shade : Two or more coats on new work	425.00	sqm	128.65	54676.00	INR Fifty Four Thousand Six Hundred & Seventy Six Only
9	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	100.00	cum	138.85	13885.00	INR Thirteen Thousand Eight Hundred & Eighty Five Only

10	Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying : (a) First layer of slurry of cement @ 0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/ sqm. This layer will be allowed to air cure for 4 hours. (b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proofing cement compound @ 0.126 kg/sqm. This layer will be allowed to air cure for 4 hours followed with water curing for 48 hours. (The rate includes preparation of surface, treatment and sealing of all joints, corners, junctions of pipes and masonry with polymer mixed slurry.)	100.00	sqm	465.60	46560.00	INR Forty Six Thousand Five Hundred & Sixty Only
11	Providing and fixing aluminium tubular handle bar 32 mm outer dia, 3.0 mm thick & 2100 mm long with SS screws etc .complete as per direction of Engineer-in-Charge. Anodized (AC 15) aluminium tubular handle bar	5.00	each	512.30	2562.00	INR Two Thousand Five Hundred & Sixty Two Only
12	Providing and fixing Brass 100mm mortice latch and lock with 6 levers without pair of handles (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	5.00	each	458.55	2293.00	INR Two Thousand Two Hundred & Ninety Three Only
13	Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete : 250x16 mm	6.00	each	231.70	1390.00	INR One Thousand Three Hundred & Ninety Only
14	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 250x10 mm	5.00	each	103.55	518.00	INR Five Hundred & Eighteen Only
15	Khargar Filling i/c compaction and transportation all complete.	30.00	cum	3043.15	91295.00	INR Ninety One Thousand Two Hundred & Ninety Five Only

16	Providing and Fixing 20 mm thick n sizes 600x600 mm, 4mm beveled edge in concealed system , easily demountable tiles in true horizontal level, suspended on inter locking metal grid of hot dipped galvanised steel sections (galvanising @ 120 grams per sqm including both side) consisting of main 'T' runner suitably spaced at joints to get required length and of size 24x38 mm made from 0.33 mm thick (minimum) sheet, spaced 1200 mm centre to centre, and cross "T" of size 24x28 mm made out of 0.33 mm (Minimum) sheet, 1200 mm long spaced between main'T' at 600 mm centre to centre to form a grid of 1200x600 mm and secondary cross 'T' of length 600 mm and size 24 x28 mm made of 0.33 mm thick (Minimum) sheet to be inter locked at middle of the 1200x 600 mm panel to from grid of size 600x600 mm, resting on periphery walls /partitions on a Perimeter wall angle pre-coated steel of size(24x24X3000 mm made of 0.40 mm thick (minimum) sheet with the help of rawl plugs at 450 mm centre to centre with 25mm long dry wall screws @ 230 mm interval, including, cutting/ making opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc., wherever required. Main 'T' runners to be suspended from ceiling using G.I. slotted cleats of size 25x35x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm G.I. adjustable rods with galvanised steel level clips of size 85 x 30 x 0.8 mm, spaced at 1200 mm centre to centre along main 'T', bottom exposed with 24mm of all Tsections shall be pre-painted with polyster baked paint, for all heights, as per specifications, drawings and as directed by Engineer-in-Charge. 85% light reflectance (of which more than 99% is diffuse reflection). The system should have Sound Absorption NRC value of 0.9 (according to EN ISO 11654). Tiles should withstand a permanent ambient RH upto 75% at 30 °C without sagging, warping or delaminating (ISO 4611). Approved make Saint Gobain or equivalent	1000.00	sqm	1858.40	1858400.00	INR Eighteen Lakh Fifty Eight Thousand Four Hundred Only
17	Providing & Fixing of FR grade acoustic stretch fabric system of size 1.20m wide shall be stretched over the grippers. The frame work consists of of Solid wooden base of 28mm thick battens and 12mm grippers. Acoustic wall panel of 40 mm thick with minimum sound absorption coefficient of 0.9 without airgap. Fabric on the panels wrapped around in concealed system with grippers and wooden battens The glass wool core of the tiles should be tested and classified as noncombustible according to EN ISO 1182 with reaction to fire classification class A2 s1 d0 according to EN 13501 - 1 - European Standard. Approved make Saint Gobain or equivalent	350.00	sqm	7026.50	2459275.00	INR Twenty Four Lakh Fifty Nine Thousand Two Hundred & Seventy Five Only
Total in Figures					6635666.00	INR Forty One Lakh Seventy Six Thousand Three Hundred & Ninety One Only
Quoted Rate in Figures			Select		0.00	INR Zero Only
Quoted Rate in Words	INR Zero Only					